

11/20/00

A

**UTILITY PATENT APPLICATION TRANSMITTAL  
(Small Entity)**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.  
27021-ATotal Pages in this Submission  
4**TO THE ASSISTANT COMMISSIONER FOR PATENTS**Box Patent Application  
Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:

**METHOD AND APPARATUS FOR REINFORCING A DOOR ASSEMBLY**

and invented by:

**OLBERDING, RONALD E., ET AL.**If a **CONTINUATION APPLICATION**, check appropriate box and supply the requisite information:☒ **Continuation** ☐ **Divisional** ☐ **Continuation-in-part (CIP)** of prior application No.: 09/272,074

Which is a:

☐ **Continuation** ☐ **Divisional** ☐ **Continuation-in-part (CIP)** of prior application No.:

Which is a:

☐ **Continuation** ☐ **Divisional** ☐ **Continuation-in-part (CIP)** of prior application No.:

Enclosed are:

**Application Elements**

1. ☒ Filing fee as calculated and transmitted as described below
2. ☒ Specification having 18 pages and including the following:
  - a. ☒ Descriptive Title of the Invention
  - b. ☒ Cross References to Related Applications (if applicable)
  - c. ☐ Statement Regarding Federally-sponsored Research/Development (if applicable)
  - d. ☐ Reference to Microfiche Appendix (if applicable)
  - e. ☒ Background of the Invention
  - f. ☒ Brief Summary of the Invention
  - g. ☒ Brief Description of the Drawings (if drawings filed)
  - h. ☒ Detailed Description
  - i. ☒ Claim(s) as Classified Below
  - j. ☒ Abstract of the Disclosure

# UTILITY PATENT APPLICATION TRANSMITTAL (Small Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.

27021-A

Total Pages in this Submission

4

## Application Elements (Continued)

3. ☒ Drawing(s) (when necessary as prescribed by 35 USC 113)
- a. ☒ Formal      b. ☐ Informal      Number of Sheets 5
4. ☒ Oath or Declaration
- a. ☐ Newly executed (original or copy)      ☐ Unexecuted
- b. ☒ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional application only)
- c. ☒ With Power of Attorney      ☐ Without Power of Attorney
- d. ☐ DELETION OF INVENTOR(S)  
Signed statement attached deleting inventor(s) named in the prior application,  
see 37 C.F.R. 1.63(d)(2) and 1.33(b).
5. ☒ Incorporation By Reference (usable if Box 4b is checked)  
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under  
Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby  
incorporated by reference therein.
6. ☐ Computer Program in Microfiche
7. ☐ Genetic Sequence Submission (if applicable, all must be included)
- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

## Accompanying Application Parts

8. ☐ Assignment Papers (cover sheet & documents)
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement/PTO-1449      ☐ Copies of IDS Citations
12. ☒ Preliminary Amendment
13. ☒ Acknowledgment postcard
14. ☒ Certificate of Mailing
- ☐ First Class      ☒ Express Mail (Specify Label No.): EL618533117US

# UTILITY PATENT APPLICATION TRANSMITTAL (Small Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.  
27021-A

Total Pages in this Submission  
4

## Accompanying Application Parts (Continued)

15. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☐ Small Entity Statement(s) - Specify Number of Statements Submitted: \_\_\_\_\_
17. ☒ Additional Enclosures (please identify below):

General Authorization Form

## Request That Application Not Be Published Pursuant To 35 U.S.C. 122(b)(2)

18. ☐ Pursuant to 35 U.S.C. 122(b)(2), Applicant hereby requests that this patent application not be published pursuant to 35 U.S.C. 122(b)(1). Applicant hereby certifies that the invention disclosed in this application has not and will not be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication of applications 18 months after filing of the application.

## Warning

**An applicant who makes a request not to publish, but who subsequently files in a foreign country or under a multilateral international agreement specified in 35 U.S.C. 122(b)(2)(B)(i), must notify the Director of such filing not later than 45 days after the date of the filing of such foreign or international application. A failure of the applicant to provide such notice within the prescribed period shall result in the application being regarded as abandoned, unless it is shown to the satisfaction of the Director that the delay in submitting the notice was unintentional.**

**UTILITY PATENT APPLICATION TRANSMITTAL**  
**(Small Entity)**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.  
27021-A

Total Pages in this Submission  
4

**Fee Calculation and Transmittal**

**CLAIMS AS FILED**

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	19	- 20 =	0	x \$9.00	\$0.00
Indep. Claims	2	- 3 =	0	x \$39.00	\$0.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$355.00
OTHER FEE (specify purpose)					\$0.00
TOTAL FILING FEE					\$355.00

- ☒ A check in the amount of **\$355.00** to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. **19-0522** as described below. A duplicate copy of this sheet is enclosed.
- ☐ Charge the amount of \_\_\_\_\_ as filing fee.
- ☒ Credit any overpayment.
- ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
- ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

Dated: November 17, 2000



Signature

Andrew G. Colombo, Reg. No. 40,565



23589

PATENT TRADEMARK OFFICE

CC:

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Application of:

OLBERDING, RONALD E., et al.

METHOD AND APPARATUS FOR  
REINFORCING A DOOR ASSEMBLY

Assistant Commissioner for Patents  
Washington, D.C. 20231

Sir:

**GENERAL AUTHORIZATION PURSUANT TO 37 C.F.R. § 1.136(a)(3)**


The Commissioner is hereby authorized to charge all required extension of time fees under 37 C.F.R. § 1.17 during the entire pendency of this application or credit any overpayment to Deposit Account No. 19-0522. This Authorization shall be treated as a constructive petition for an extension of time in any concurrent or future reply requiring a petition for an extension of time under 37 C.F.R. § 1.136(a) for its timely submission.

It should be noted that the undersigned has authorized the Commissioner to charge the payment of additional fees in the accompanying transmittal letter

Respectfully submitted,

HOVEY, WILLIAMS, TIMMONS, & COLLINS

By:

  
\_\_\_\_\_  
Andrew G. Colombo, Reg. No. 40,565  
2405 Grand Boulevard, Suite 400  
Kansas City, Missouri 64108  
(816) 474-9050

ATTORNEYS FOR APPLICANT

(Docket No. 27021-A)

**CERTIFICATE OF MAILING BY "EXPRESS MAIL" (37 CFR 1.10)**

Applicant(s): OLBERDING, RONALD E., et al.

Docket No.  
27021-A

Serial No.

Filing Date

Examiner

Group Art Unit

Thissell, J.


3635

Invention: METHOD AND APPARATUS FOR REINFORCING A DOOR ASSEMBLY

I hereby certify that this Continuation Application; Preliminary Amendment; Copy of Prior Application; 5 drawing sheets; Copy of Prior Signed Declaration and Power of Attorney; General Authorization Form; Copy of Prior Signed Small Entity Form; \$355.00 filing fee; and return postcard is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 in an envelope addressed to: Box Patent Application, The Assistant Commissioner for Patents, Washington, D.C. 20231 on November 17, 2000.

Jen Krygiel

(Typed or Printed Name of person Mailing Correspondence)

  
(Signature of Person Mailing Correspondence)EL618533117US

("Express Mail" Mailing Label Number)

Applicant or Patentee: OL RDING, RONALD E., et al.	Attorney's Docket No.: 27021
Serial or Patent No.:	Filed or Issued:
For: METHOD AND APPARATUS FOR REINFORCING A DOOR ASSEMBLY	

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS  
(37 CFR 1.9(f) AND 1.27(c)) - SMALL BUSINESS CONCERN**

I hereby declare that I am

- ☐ the owner of the small business concern identified below:  
☒ an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF CONCERN	EDWARD WAYNE, INC.
ADDRESS OF CONCERN	10308 Metcalf Avenue, Suite 308, Overland Park, KS 66212

I hereby declare that the above-identified small business concern qualifies as a small business concern as defined in 13 CFR 121.3-18, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees under Section 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention, entitled METHOD AND APPARATUS FOR REINFORCING A DOOR ASSEMBLY by inventor(s) RONALD E. OLBERDING and DAVID W. ALLEN described in

- ☒ the specification filed herewith.  
☐ application serial no. \_\_\_\_\_, filed \_\_\_\_\_.  
☐ patent no. \_\_\_\_\_, issued \_\_\_\_\_.

If the rights held by the above-identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed below\* and no rights to the invention are held by any person, other than the inventor, who could not qualify as a small business concern under 37 CFR 1.9(d) or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Name
Address
<input type="checkbox"/> Individual <input type="checkbox"/> Small Business Concern <input type="checkbox"/> Nonprofit Organization
Name
Address
<input type="checkbox"/> Individual <input type="checkbox"/> Small Business Concern <input type="checkbox"/> Nonprofit Organization

\*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING	Mr. Ronald E. Olberding
TITLE OF PERSON OTHER THAN OWNER	
ADDRESS OF PERSON SIGNING	1118 Oak Street, Kansas City, Missouri 64114

SIGNATURE Ronald E. Olberding DATE 3-18-99

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Application of:

OLBERDING, RONALD E., et al.

METHOD AND APPARATUS FOR  
REINFORCING A DOOR ASSEMBLY

) Examiner: Thissell, J.  
) Group Art Unit No. 3635  
)  
)  
)  
)  
)

---

Assistant Commissioner for Patents  
Washington, D.C. 20231

Sir:

**PRELIMINARY AMENDMENT**

Please enter this Amendment in the above-referenced application before substantive examination.

**IN THE SPECIFICATION:**

In line 2 of page 4, please delete the last word "and".

In line 5 of page 4, please delete the "." at the end of the sentence and insert therefor --; and--.

In line 6 of page 4, please insert the following paragraph --FIG. 9 is a fragmentary perspective view of the alternative fenestration product assembled with the door assembly and the second sidelight assembly, particularly illustrating the reinforcement plate located between the window jamb and the hinge side door jamb.--

In line 31 of page 11, please delete the text "(not shown)".



In line 34 of page 11, following the last sentence of the paragraph, please insert the text --Such an arrangement is shown in FIG. 9, wherein the fenestration product 200 is provided with a second sidelight assembly 230 along the hinge side of the door assembly 202. As indicated, a reinforcement plate 232 is located between the door jamb 234 and the window jamb 236 and the jambs 234 and 236 are interconnected by corrugated staples 238. Furthermore, the hinges 240 (only two being shown in FIG. 9) of the door assembly 202 are securely fastened to the reinforcement plate 232 by suitable fasteners 242. The fasteners 242 may also threadably interengage the door jamb 234 and window jamb 236 similar to the strike side of the door assembly 202.--

**IN THE CLAIMS:**

Please cancel claims 1-19 without prejudice or disclaimer and add new claims 20-38 as follows:

20. A fenestration product comprising:
- a door assembly including a door and a pair of laterally spaced, structural jambs,
  - said door assembly further including door hardware configured to associate the door with the jambs, said door hardware including a strike plate fixed relative to a strike-side one of the jambs and a hinge fixed relative to a hinge-side one of the jambs to swingably mount the door on the hinge-side jamb;
  - a sidelight assembly alongside the door assembly; and
  - a reinforcement plate secured to the hinge-side jamb and configured to restrict movement of the hinge relative to the hinge-side jamb.

21. A fenestration product as claimed in claim 20; and  
an additional reinforcement plate secured to the strike-side jamb and configured to restrict  
movement of the strike plate relative to the strike-side jamb.

22. A fenestration product as claimed in claim 21,  
said sidelight assembly being adjacent the hinge-side jamb; and  
an additional sidelight assembly adjacent the strike-side jamb.

23. A fenestration product as claimed in claim 20,  
said jambs each presenting an inner face facing inwardly toward the door when the door is  
in a closed position and a generally oppositely facing outer face,  
said reinforcement plate being secured flatly against at least one of the faces of the hinge-  
side jamb.

24. A fenestration product as claimed in claim 23,  
said sidelight assembly including a window jamb positioned alongside the outer face of an  
adjacent one of the door jambs,  
said window jamb and the adjacent door jamb being interconnected.

25. A fenestration product as claimed in claim 24; and  
an additional reinforcement plate secured flatly against at least one of the faces of the strike-  
side jamb and configured to restrict movement of the strike plate relative to the  
strike-side jamb.

26. A fenestration product as claimed in claim 25,  
said additional reinforcement plate being secured flatly at least in part against the outer face  
of the strike-side jamb,  
said strike plate being fixed to the additional reinforcement plate.

27. A fenestration product as claimed in claim 26,  
said sidelight assembly being adjacent the hinge-side jamb; and  
an additional sidelight assembly including an additional window jamb adjacent the outer face  
of the strike-side jamb, with the additional window jamb and the strike-side jamb  
being interconnected,  
each of said reinforcement plates being located at least in part between the respective ones  
of the adjacent and window jambs.

28. A fenestration product as claimed in claim 23,  
said reinforcement plate being secured flatly at least in part against the outer face of the  
hinge-side jamb.

29. A fenestration product as claimed in claim 23,  
said hinge including a pair of relatively swingable interconnected hinge plates, one of the  
hinge plates being positioned along the inner face of the hinge-side jamb,  
said one of the hinge plates being fixed to the reinforcement plate.

30. A method of reinforcing a fenestration product including a door and a pair of laterally spaced, structural jambs, said fenestration product reinforcement method comprising the steps of:

- (a) fixing a strike plate relative to a strike-side one of the jambs and a hinge relative to a hinge-side one of the jambs;
- (b) placing a window adjacent one of the jambs; and
- (c) reenforcing the hinge-side jamb in such a manner that movement of the hinge relative to the hinge-side jamb is restricted.

31. A fenestration product reinforcement method as claimed in claim 30; and

- (d) reinforcing the strike-side jamb in such a manner that movement of the strike plate relative to the strike-side jamb is restricted.

32. A fenestration product reinforcement method as claimed in claim 31,

- step (b) including the step of placing the window adjacent the hinge-side jamb; and
- (e) placing an additional window adjacent the strike-side jamb.

33. A fenestration product reinforcement method as claimed in claim 31,

- step (c) including the step of securing a reinforcement plate to the hinge-side jamb,
- step (d) including the step of securing a reinforcement plate to the strike-side jamb.

34. A fenestration product reinforcement method as claimed in claim 30,

said jambs each presenting an inner face facing inwardly toward the door when the door is

in a closed position and a generally oppositely facing outer face,  
step (c) including the step of securing a reinforcement plate against at least one of the faces  
of the hinge-side jamb.

35. A fenestration product reinforcement method as claimed in claim 34,  
step (c) including the step of securing at least part of the reinforcement plate flatly against  
the outer face of the hinge-side jamb.

36. A fenestration product reinforcement method as claimed in claim 34,  
said hinge including a pair of relatively swingable interconnected hinge plates,  
step (c) including the step of fixing one of the hinge plates of the hinge to the reinforcement  
plate.

37. A fenestration product reinforcement method as claimed in claim 34;  
(d) securing an additional reinforcement plate flatly against at least one of the faces of  
the strike-side jamb; and  
(e) fastening a portion of the strike plate to said additional reinforcement plate.

38. A fenestration product reinforcement method as claimed in claim 37,  
step (b) including the steps of placing a window jamb adjacent the hinge-side jamb,  
interconnecting the window jamb and the hinge-side jamb, and supporting the  
window on the window jamb; and  
(f) placing an additional window jamb adjacent the strike-side jamb, interconnecting the

additional window jamb and the strike-side jamb, and supporting an additional window on the additional window jamb,  
steps (c) and (d) each including the step of positioning the respective reinforcement plate at least partly between the corresponding ones of the window and door jambs.

**REMARKS:**

Claims 1-19 have been canceled without prejudice or disclaimer and claims 20-38 have been added so that claims 20-38 are presently pending. Of the pending claims, claims 20 and 30 are independent.

It is respectfully submitted that the invention recited in claims 20-38 are believed to be patentable over the prior art references. Thus, the present application is believed to be in condition for allowance and such allowance is courteously requested.

Should the Examiner have questions, the undersigned may be contacted at (800) 445-3460. The Commissioner is hereby authorized to charge any payment due in connection with this Amendment to Deposit Account No. 19-0522.

Respectfully submitted

HOVEY, WILLIAMS, TIMMONS & COLLINS

By: 

Andrew G. Colombo, Reg. No. 40,565  
2405 Grand Boulevard, Suite 400  
Kansas City, Missouri 64108

ATTORNEYS FOR APPLICANT

(Docket No. 27021-A)

## METHOD AND APPARATUS FOR REINFORCING A DOOR ASSEMBLY

### RELATED APPLICATION

This is a continuation of Application Serial No. 09/272,074, filed March 18, 1999.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates generally to fenestration products, such as a door assembly, for installation into a building. More particularly, the present invention concerns a reinforced fenestration product design that utilizes standard door hardware but still reduces the risk of intrusion through the product.

#### 2. Discussion of Prior Art

The security of a building is highly dependent on the ability of an exterior door assembly to withstand large impact loads exerted against the outside of the door. This has previously been identified in our co-pending applications for U.S. Letters Patent Serial No. 08/864,547, filed May 28, 1997, entitled REINFORCED FENESTRATION PRODUCT; Serial No. 09/136,990, filed August 20, 1998, entitled REINFORCEMENT MEMBER FOR A FENESTRATION PRODUCT; Serial No. 09/137,023, filed August 20, 1998, entitled METHOD OF REINFORCING A DOOR; and Serial No. 09/128,517, filed August 3, 1998, entitled IMPROVED STRIKE PLATE FOR A DOOR ASSEMBLY; all of which are assigned of record to the assignee of the present application. It is noted that these prior applications disclose various inventions that improve the security provided by a fenestration product. As particularly indicated in the '517 application, there is still a risk of intrusion through a conventional door assembly, even though one or both of the door jambs has been reinforced. Specifically, it has been determined that a large impact load exerted against the exterior side of the door may cause the door latch bolt and lock bolt to fail (e.g., bend). This is believed to be attributable to the fact that a conventional door assembly will often require the distal ends of the latch bolt and, more importantly, the lock bolt to resist movement of the door when a large impact load is exerted against the exterior side of the door. There will consequently be a large moment experienced by the bolts, and they therefore have a tendency to fail (e.g., bend) under these conditions.

## OBJECTS AND SUMMARY OF THE INVENTION

Responsive to these and other problems, an important object of the present invention is to provide an improved fenestration product that reduces the risk of intrusion therethrough. It is also an object of the present invention to provide an inexpensive and simple method of reinforcing a fenestration product. It is particularly an important object of the present invention to provide a reinforced fenestration product designed to prevent intrusion therethrough, without requiring new door latch or lock designs. In this respect, an important object of the present invention is to provide a fenestration product that is designed to prevent the door latch bolt and lock bolt from experiencing large moments when an impact load is exerted against the exterior side of the door. Another important object of the present invention is to provide such a fenestration product, with the product utilizing standard door hardware.

In accordance with these and other objects evident from the following description of the preferred embodiment, the present invention concerns a door assembly including a generally flat door jamb that presents an inwardly facing inner face and a generally oppositely facing outer face. A reinforcement plate is secured flatly against the outer face of the door jamb. Moreover, the door hardware (e.g., hinges and/or strike plates) positioned along the inner face of the door jamb are fastened to the reinforcement plate so that movement relative to the reinforcement plate and door jamb is prevented.

It is believed that this inventive arrangement essentially prevents dislodgement of standard door hardware when an impact load is exerted against the exterior side of the door. That is to say, the standard door hardware on the reinforced door assembly does not become the weak point of the product. This not only serves to reinforce the jamb to which the hardware is attached, but it also significantly reduces the risk of intrusion often associated with standard hardware failure. With particular respect to the strike plate, it has been determined that the inventive arrangement substantially decreases the moment experienced by the door latch bolt and lock bolt when a large impact load is exerted against the exterior side of the door, whereby failure of the door lock and door latch is virtually eliminated. In other words, because the strike plate is retained in the intended location, the door latch bolt and lock bolt resist movement of the door (e.g., when a large impact load is exerted against the exterior side of the door) generally at their respective bases (i.e., at a point along their respective



lengths adjacent the side of the door), rather than adjacent their distal ends, as particularly described in the '517 application.

If desired, a sidelight assembly may be associated with the door assembly, with one of the window jambs being connected to the door jamb in such a manner that the reinforcement plate is located between the adjacent window and door jambs. The present invention is also concerned with an inventive method of reinforcing a door assembly, wherein the door hardware is fastened to the reinforcement plate secured flatly against the outer face of the door jamb.

Other aspects and advantages of the present invention will be apparent from the following detailed description of the preferred embodiments and the accompanying drawing figures.

#### BRIEF DESCRIPTION OF THE DRAWING FIGURES

Preferred embodiments of the invention are described in detail below with reference to the attached drawing figures, wherein:

FIG. 1 is a fragmentary perspective view of a fenestration product constructed in accordance with the principles of the present invention, particularly illustrating the product installed in a traditional opening in the structural framework of a building;

FIG. 2 is an exploded perspective view of the fenestration product, with the door being removed and particularly illustrating the shimming preferably used with the product;

FIG. 3 is an enlarged, fragmentary perspective view of the strike side of the fenestration product when installed, particularly illustrating the preferred shimming being exploded away from the remaining components and the strike plates being fastened to the reinforcement plate;

FIG. 4 is a fragmentary elevational view of the interior side of the fenestration product when installed, with parts being sectioned to illustrate the strike plates associating the door with the door jamb and being fastened to the reinforcement plate;

FIG. 5 is an enlarged, fragmentary perspective view of the hinge side of the fenestration product when installed, particularly illustrating the preferred shimming being exploded away from the remaining components and the hinge being fastened to the reinforcement plate;

FIG. 6 is a fragmentary elevational view of the interior side of the fenestration product when installed, with parts being sectioned to illustrate the hinge associating the door with the door jamb and being fastened to the reinforcement plate;

FIG. 7 is a perspective view of an alternative reinforcement plate configured for use in a fenestration product including a door assembly and sidelight assembly, particularly illustrating the fastener-receiving openings in the reinforcement plate and the various fasteners used to secure the plate to the door jamb and to interconnect the adjacent door and window jambs; and

FIG. 8 is a fragmentary perspective view of the alternative fenestration product assembled with the door assembly and sidelight assembly, particularly illustrating the strike plates being fastened to the reinforcement plate.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Turning initially to FIG. 1, the first fenestration product 10 selected for illustration generally comprises a door assembly 12 designed to be installed within the traditional opening 14 defined by a building framework 16. In particular, the traditional opening 14 is cooperatively defined by a pair of laterally spaced cripple studs 18 and 20, the sub-floor (not shown), and a header 22. As is customary, the cripple studs 18 and 20 are traditionally formed of wooden planks referred to as "two-by-fours", the sub-floor is formed of plywood or pressboard supported on suitable joists (not shown), and the header is formed by a pair of attached wooden planks referred to as "two-by-sixes". The header 22 is typically supported between a pair of laterally spaced wall studs 24 and 26 extending between the base plate 28 and top plates 30 and 32. It is noted that the studs 24, 26 and plates 28, 30, 32 are all typically formed of two-by-fours. The cripple studs 18 and 20 are fixed to the wall studs 24 and 26 along the respective interior sides thereof and extend from the sub-floor to the header 22.

Those ordinarily skilled in the art will appreciate that the illustrated framework 16 has been provided for illustrative purposes only. That is, it is entirely within the ambit of the present invention to install the fenestration product 10 in buildings having various other constructions. Moreover, it shall be understood that the term "building" as used herein means any structure having an area which may be accessed through a door assembly (e.g., houses, multi-dwelling structures, commercial structures, etc.).

With the foregoing caveat in mind, the illustrated door assembly 12 includes an open framework comprising a pair of laterally spaced flat door jambs 34 and 36 extending between the sub-floor and header 22, an upper cross-beam 38 fixed between the upper ends of the jambs 34 and 36 to be located adjacent the header 22 when the product is installed, and a sill 40 extending between the lower ends of the jambs 34 and 36 for attachment to the sub-floor (see FIG. 2). The jambs 34,36 and cross-beam 38 are illustrated as an integral, seamless body, although it will be appreciated that these components are normally separate pieces of material that are interconnected by suitable means, such as screws. It is noted that the illustrated door framework is formed of wood, as this is the material most commonly used and most susceptible to failure when a large impact load is exerted against the exterior side of the assembly.

The door assembly 12 further includes a door 42 swingably mounted to the jamb 34, with the door 42 being configured to fit within the framework when swung to a closed position (see FIGS. 4 and 5). A stop 44 extends along the inner faces of the jambs 34,36 and crossbeam 38 for preventing, among other things, outward swinging movement of the door 42 beyond its closed position. The stop 44 traditionally comprises wood planks having a width that is less than that of the jambs 34,36 and crossbeam 38. The illustrated stop 44 is mounted flush with the exterior side of the jambs 34,36 and crossbeam 38 and is dimensioned so that the interior side of the door 42 lies flush with the interior side of the jambs 34,36 and crossbeam 38 when the door 42 is closed.

The door jamb 36 is provided with a pair of vertically spaced bolt-receiving holes 46 and 48. In the usual manner, the door 42 is provided with a latch mechanism 50 having a bolt 52 that is yieldably urged outwardly to be automatically inserted into the lower hole 48 when the door 42 is closed, whereby the latch bolt 52 serves to releasably retain the door 42 in the closed position. Rotatable interior and exterior handles 54 and 55 are operably coupled with the latch bolt 52 to retract the latter into the door 42 and out of the hole 48 when it is desired to swing the door 42 out of the closed position. The door 42 further includes a lock mechanism 56 for securely locking the door 42 in its closed position. Similar to the latch mechanism 50, the lock mechanism 56 is provided with a reciprocating bolt 58 that is shiftable into and out of the upper jamb hole 46, although it is noted that the lock bolt 58 has a relatively longer throw than the latch bolt 52 (see FIG. 4) and the lock bolt 58 is typically not

automatically extended out of the door 42. As is customary, the lock bolt 58 is shifted between the locked and unlocked positions by an interior hand-operated turn screw 60, as well as by a key-operated cylinder (not shown) on the exterior side of the door 42.

In the usual manner, the door assembly 12 includes various hardware for associating the door 42 with the door jambs 34 and 36. As will subsequently be described, the door hardware preferably has a standard and conventional construction, however, it is not susceptible to the problem of dislodgement often associated with traditional door assemblies. The hardware of the illustrated door assembly 12 includes three hinges 62,64,66 and a pair of strike plates 68 and 70. In the usual manner, the hinges 62,64,66 serve to swingably mount the door 42 on the jamb 34, while the strike plates 68,70 serve to, among other things, reinforce the jamb 36 in the vicinity of the bolt-receiving holes 46,48.

With particular respect to the hinges 62-66, this hardware has a universal construction, and it is consequently sufficient to describe only one of the hinges with the understanding that the remaining hinges are similarly constructed. As shown in FIGS. 5 and 6, the intermediate hinge 64 includes relatively swingable first and second plates 72 and 74 that are fixed relative to the door jamb 34 and door 42, respectively. As is customary, each of the plates 72 and 74 have spaced apart tubular sections, whereby the plates 72 and 74 cooperatively present a sleeve 76 configured to receive a pin 78 therein. In addition, each of the plates 72 and 74 are provided with a series of screw-receiving openings configured to receive suitable fasteners for mounting the plates 72 and 74, as set forth hereinbelow. If desired, the jamb 34 and door 42 may be provided with recesses configured to snugly receive the respective plates 72 and 74.

As perhaps best shown in FIGS. 3 and 4, the upper strike plate 68 comprises a generally flat body having a bolt-receiving opening 80 defined therein. The strike plate 68 is positioned along the inner face of the jamb 36 in such a location that the bolt receiving opening 80 is aligned with the hole 46 defined in the jamb 36. If desired, the strike plate 68 may be recessed in the jamb 36, as shown in FIG. 4. It is noted that the shape and size of the bolt-receiving opening 80 corresponds with that of the lock bolt 58 in such a manner that movement of the bolt 58 in a direction transverse to its longitudinal axis is significantly limited by the plate 68, when the bolt 58 is received in the opening 80. In fact, the strike plate 68 may be designed so that the lock bolt 58 is slidably received within the opening 80. It will be appreciated that the relative shapes and sizes of the lock bolt 58 and opening 80 may vary to some degree,

although it is important that the plate 68 be configured to prevent virtually any movement of the bolt in a direction corresponding to opening of the door 42, which is customary. Similar to the lock strike plate 68, the latch strike plate 70 comprises a generally flat body having a bolt receiving opening 82 that is aligned with the hole 48 in the jamb 36 and that has a shape and size preferably corresponding to that of the latch bolt 52. However, the latch strike plate 70 is provided with a cam element 84 that projects from the interior side of the body. In the usual manner, the cam element 84 is designed to engage the latch bolt 52 and cause the same to retract, as the door 42 is closed. It is noted that both strike plates 68 and 70 are provided with screw-receiving holes spaced above and below the respective bolt-receiving openings 80 and 82.

A pair of reinforcement plates 86 and 88 are associated with respective ones of the door jambs 34 and 36. The plates 86 and 88 are similar to the reinforcement structure shown in the '547, '990 and '023 applications, which are incorporated by reference herein. Not only do the plates 86 and 88 afford the advantages identified in these applications, they also provide a strong anchoring point for the door hardware, as will subsequently be described.

Turning first to the hinge side reinforcement plate 86, this component comprises a flat, rectangular body that fits conveniently in the normal space provided between the cripple stud 18 and door jamb 34. The plate 86 is preferably formed of an approximately 1/8 inch thick piece of aluminum. The illustrated plate 86 has a length of approximately seventy-six inches and a width of approximately three inches. Although the plate 86 is shorter and narrower than the illustrated door jamb 34, it will be appreciated that the preferred dimensions fit virtually all door jamb sizes. That is to say, the plate 86 is dimensioned so that it does not project beyond the boundaries of a traditional door jamb. In addition, the preferred plate length ensures that the plate 86 will extend substantially the full length of virtually any door jamb. If desired, the plate 86 may alternatively be dimensioned to be coextensive with the door jamb 34. In any case, the reinforcement plate 86 is secured flatly against the outer face of the door jamb 34, preferably with the lower ends and interior sides of the jamb 34 and plate 86 being flush. In the illustrated embodiment, the plate 86 is initially secured to the jamb 34 by three mounting screws 90 that are received in respective openings 92 defined in the plate 86 and threaded into the jamb 34. The screws 90 are preferably countersunk in the plate 86 and may comprise standard one inch wood screws. The reinforcement plate 86 is further provided with four longitudinally spaced attachment screw openings 94.

Preferably, the reinforcement plate 86 is used as a template to form by suitable means, such as drilling, the openings 96 in the jamb 34. Each set of aligned openings 94 and 96 is configured to received an attachment screw 98 therein. As perhaps best shown in FIGS. 5 and 6, the attachment screws 98 have sufficient length to pass through the jamb 34 and plate 86 and then thread into the adjacent cripple stud 18. Of course, the attachment screws 98 are inserted during installation of the fenestration product 10 in the building framework 16. The jamb 34 and reinforcement plate 86 also cooperatively present aligned fastening screw openings 100 and 102, respectively. The fastening screw openings 100 and 102 are preferably formed when the hinges 62,64,66 are mounted, although it is entirely within the ambit of the present invention to provide these openings prior to hardware installation.

In particular, the hinges 62,64,66 are positioned along the inner face of the jamb 34 in the illustrated locations, with the positioning of the hinges being facilitated as a result of the recesses formed in the jamb, as noted above. The first plate 72 of each hinge is then preferably used as a template to facilitate formation of the openings 100 and 102, with the openings being formed by suitable means (e.g., drilling). In addition, although the first plate 72 of each of the illustrated hinges 62,64,66 is provided with four screw-receiving openings, each of the first plates is associated with only two sets of aligned openings 100,102. In this respect, it is entirely within the ambit of the present invention to vary the number of sets of aligned openings 100,102 associated with each of the hinges (e.g., the upper hinge 62 may be associated with three sets of aligned openings 100,102). In any case, a fastening screw 104 is inserted through the first plate 72 of each of the hinges 62,64,66 and into each set of aligned openings 100,102. In the illustrated embodiment, the screw 104 and openings 100,102 are cooperatively designed so that the screw 104 threadably engages the reinforcement plate 86 and jamb 34 along the respective openings 100 and 102. Preferably, the screw 104 comprises a standard thread cutting screw and the openings 100,102 are standard pilot holes dimensioned to receive the screw 104 as it forms the threads in the jamb 34 and reinforcement plate 86. It is noted that the corresponding openings in the first plate 72 of each of the hinges 62,64,66 is relatively larger than the openings 100,102, such that the screw 104 is slidably received within each of these openings. In other words, the illustrated hinges 62,64,66 do not threadably engage the screws 104, although it is entirely within the ambit of the invention to do so. It is also possible to vary the size of the opening 102 defined in the jamb 34 so that the screw 104

is slidably received within the jamb 34 rather than being threadably interengaged therewith.

However, it is important that each of the hinges 62,64,66 be securely fastened to the reinforcement plate 86. Particularly, each of the hinges 62,64,66 is prevented from shifting relative to the plate 86 as a result of the interlocking threaded interengagement of the screws 104 and reinforcement plate 86. The hinges 62,64,66 are otherwise separate and disconnected from the reinforcement plate 86, which consequently permits the use of standard hinges in the door assembly 12. It is noted that the reinforcement plate 86 is particularly well suited for use with the thread cutting screws 104 as a result of the plate 86 being formed of metal, such as the preferred aluminum material. Moreover, the principles of the present invention are equally applicable to various other arrangements for securely fastening standard hinges to the reinforcement plate 86. For example, the reinforcement plate 86 may be provided with a previously internally threaded opening that is configured to receive an externally threaded bolt, with such an arrangement likewise benefitting from the reinforcement plate being formed of metal.

As shown in FIGS. 5 and 6, the first plate 72 of each of the hinges 62,64,66 is further secured to the door jamb 34 by relatively short screws 106 received within the remaining openings of the first plate 72. As is customary, the second plate 74 of each of the hinges 62,64,66 is fixed to the door 42 by screws 108, which may vary in length as shown.

The strike plate side reinforcement plate 88 is similar in design and function to the hinge side reinforcement plate 86. Thus, it shall be sufficient to explain that the strike plate side reinforcement plate 88 is secured against the outer face of the jamb 36 by mounting screws 110 received within respective openings 114 defined in the plate 88 (see FIG. 2). The strike plate side reinforcement plate 88 further includes a series of attachment screw openings 94 that are preferably used in forming aligned openings 116 in the jamb 36. Each set of openings 114,116 receive an attachment screw 118 that is threaded into the adjacent cripple stud 20 when the product 10 is installed within the building framework (see FIG. 4). Moreover, the jamb 36 and reinforcement plate 88 include aligned fastening screw openings 120 (only the openings being shown in the reinforcement plate) that are formed by suitable means, such as drilling, preferably using the strike plates 68 and 70 as templates. A plurality of fastening screws 122, which preferably comprise standard thread cutting screws, are

slidably received within the openings of the strike plates 68 and 70 and threadably engage the door jamb 36 and reinforcement plate 88 along the aligned openings 120 (see also FIGS. 3 and 4). Again, the foregoing arrangement provides advantages, and may have constructional variations, similar to those noted above with respect to the hinge side reinforcement plate 86. For example, the foregoing arrangement permits standard strike plates to be securely fastened to the reinforcement plate 88. It is also noted that the strike plate side reinforcement plate 88 is provided with a bolt-receiving opening 124 that is configured to receive the outermost end of the lock bolt 58 when the door is locked 42 in the closed position.

The inventive method of reinforcing the door assembly 12 should be apparent from the previous description. It is therefore sufficient to explain that the reinforcement plates 86 and 88 are first placed against the outer faces of the respective door jambs 34 and 36. It may be necessary to shift the plates 86 and 88 along the outer faces of the respective jambs 34 and 36 until certain openings and/or edges are aligned. For example, the lower end and interior side of the hinge side reinforcement plate 86 are positioned generally flush with the corresponding end and side of the jamb 34, in the illustrated embodiment. On the other hand, the bolt-receiving opening 124 and interior side of the strike plate side reinforcement plate 88 are respectively aligned with the bolt-receiving hole 46 and interior side of the jamb 36. The reinforcement plates 86 and 88 are then secured to the jambs 34 and 36 by the mounting screws 90 and 110, respectively. The attachment screw openings 96 and 116 are then formed in the jambs 34 and 36, using the openings 94 and 114 in the reinforcement plates 86 and 88 as templates. In most instances, the previous steps would be performed at the mill or factory, although it is entirely within the ambit of the present invention to perform all of the steps in the field (i.e., at the building construction site) or at the factory. In any case, the product 10 is then preferably set within the opening 14 of the building framework 16. This may require temporary attachment of the door framework to the building framework, such as by nailing the former to the latter, and the door assembly 12 is shimmed within the opening 14. In the illustrated embodiment, shims 126, 128, 130 are wedged into the spaced defined between the cripple stud 18 and reinforcement plate 86, with each of the shims being vertically aligned with a respective one of the hinges (see FIGS. 2, 5 and 6). On the opposite side, shims 132, 134, 136, 138 are wedged between the cripple stud 120 and reinforcement plate 88, with each of these shims being generally vertically aligned with one of the attachment screws 118. Two



shims 140 and 142 are preferably wedged between the header 22 and cross-beam 38, with a pair of attachment screws 144 being provided to securely fasten the cross-beam 38 to the header 22. At this point, the door hardware (i.e., the hinges 62,64,66 and strike plate 68,70) is preferably installed. As noted above, the preferred method involves first forming pilot holes in the respective door jamb and reinforcement plate using the door hardware as a template. The fastening screws 104 or 122 are subsequently inserted through the corresponding hardware and then threaded into the respective door jamb and reinforcement plate. Of course, attachment of the door hardware need not occur after the door assembly 12 has been set in the building framework 16, but rather such attachment may occur as soon as the reinforcement plates 86 and 88 have been mounted to the respective door jambs 34 and 36. Finally, the product 10 is securely attached to the building framework 16 by installing the attachment screws 98,118,144.

It will be appreciated that this installation virtually eliminates intrusion that might otherwise be achieved by exerting a large impact load on the exterior side of the door 42. Not only is the door framework, especially the jambs 34 and 36, reinforced, but the standard door hardware is securely mounted so as not to be dislodged during such an intrusion. With particular respect to the strike plates 68 and 70, the latch bolt 52 and lock bolt 58 are not required to resist movement of the door 42 out of its closed position solely at their respective outermost ends. Instead, the strike plates 68 and 70 engage the lock bolt 58 and latch bolt 52, respectively, much closer to the door 42 to which the bolts are mounted. The moments experienced by the bolts 52 and 58 is consequently not likely to cause failure (e.g., bending of the bolts 52 and 58).

The principles of the present are equally applicable to various other fenestration product designs. For example, FIGS. 7 and 8 depict a fenestration product 200 including door assembly 202 and an adjacent sidelight assembly 204. In the usual manner, the sidelight assembly 204 includes framework 206 for supporting a window 208, with the framework 206 including a jamb 210 positioned alongside the adjacent door jamb 212. The reinforcement plate 214 is consequently located between the adjacent window and door jambs 210,212. Similar to the previous embodiment, the reinforcement plate 214 is secured to the outer face of the door jamb 212 by mounting screws 216 inserted through respective openings 218 spaced along the length of the plate 214. In addition, the interior side of the reinforcement plate 214 is provided with a series of spaced apart semicircular slots 220, each of which is configured to receive

a corrugated staple 222 therein. In this respect, the reinforcement plate 214 is preferably secured to the outer face of the door jamb 212, and the window jamb 210 is then placed alongside the door jamb 212 and connected thereto by the staples 222. Similar to the previously described embodiment, the strike plates 224 and 226 are  
5 securely fastened to the reinforcement plate 214 by suitable fasteners 228, which may also threadably interengage the door jamb 212 and window jamb 210 if desired. Although not shown, it will be appreciated that the hinges of the door assembly 202 are securely fastened to a reinforcement plate in a manner similar to the previously described embodiment. It is also noted that the fenestration product 200 may be  
10 provided with a second sidelight assembly (not shown) positioned adjacent the hinge side of the door assembly 202, with the adjacent window and door jambs being secured to one another in a manner similar to that described with respect to the present embodiment.

The preferred forms of the invention described above are to be used as illustration only, and should not be utilized in a limiting sense in interpreting the scope of the present invention. Obvious modifications to the exemplary embodiments, as hereinabove set forth, could be readily made by those skilled in the art without departing from the spirit of the present invention.

The inventors hereby states their intent to rely on the Doctrine of  
15  
20  
Equivalents to determine and assess the reasonably fair scope of the present invention as pertains to any apparatus not materially departing from but outside the literal scope of the invention as set forth in the following claims.

What is claimed is:

1. A fenestration product comprising:

5 a door assembly including at least one generally flat door jamb presenting an inwardly facing inner face and a generally oppositely facing outer face, and door hardware positioned along said inner face; and  
a substantially flat reinforcement plate secured flatly against the outer face of the door jamb,  
said door hardware having at least a portion thereof that is fastened to the  
10 reinforcement plate so that said at least a portion of the door hardware is prevented from moving relative to the reinforcement plate and away from or along the inner face of said at least one door jamb.

2. A fenestration product as claimed in claim 1,

15 said door assembly including a door shiftable into and out of a closed position, with the inner face of said at least one door jamb facing generally toward the door when the door is in the closed position,  
said door hardware being configured to associate the door with said at least one door jamb.

3. A fenestration product as claimed in claim 1,

20 said door hardware comprising at least one hinge having a pair of relatively swingable plates, one of which is positioned along the inner face of said at least one door jamb and is fastened to the reinforcement plate.

4. A fenestration product as claimed in claim 1,

25 said at least one door jamb including a bolt-receiving hole,  
said door hardware comprising at least one strike plate including a substantially flat body that is positioned flatly against the inner face of said at least one door jamb and is fastened to the reinforcement plate,  
30 said body having a bolt-receiving opening that is aligned with bolt-receiving hole in said at least one door jamb.

5. A fenestration product as claimed in claim 1,  
said reinforcement plate extending along substantially the full length of said at  
least one door jamb.

5 6. A fenestration product as claimed in claim 1; and  
at least one fastener projecting through said at least one door jamb and  
interconnecting the reinforcement plate and said at least a portion of the  
door hardware to prevent movement of the latter relative to the former.

10 7. A fenestration product as claimed in claim 6,  
said at least a portion of the door hardware, said at least one door jamb, and said  
reinforcement plate having aligned openings that receive said at least  
one fastener therein.

15 8. A fenestration product as claimed in claim 7,  
said at least one fastener comprising a screw,  
said screw threadably engaging the reinforcement plate along the opening  
defined therein.

20 9. A fenestration product as claimed in claim 8,  
said screw being slidably received within the opening defined in said at least a  
portion of the door hardware and threadably engaging said at least one  
door jamb along the opening defined therein.

25 10. A fenestration product as claimed in claim 9,  
said screw being configured to form threads in said at least one door jamb and  
the reinforcement plate as the screw is inserted into the openings defined  
therein.

30 11. A fenestration product as claimed in claim 1; and  
a sidelight assembly including at least one window jamb positioned alongside  
said at least one door jamb so that the reinforcement plate is located  
therebetween,

said at least one window jamb and said at least one door jamb being interconnected.

5           12.     A fenestration product as claimed in claim 11,  
said reinforcement member including a plurality of staple-receiving slots; and  
a plurality of staples, each of which is received within a respective one of the  
staple-receiving slots and serves to interconnect said at least one  
window jamb and said at least one door jamb.

10           13.     A fenestration product as claimed in claim 1,  
said reinforcement plate being formed of metal.

14. A method of reinforcing a fenestration product including a generally flat door jamb that presents an inwardly facing inner face and a generally oppositely facing outer face, said fenestration product reinforcement method comprising the steps of:

- (a) securing a substantially flat reinforcement plate against the outer face of the door jamb;
- (b) positioning door hardware against an inner face of the door jamb; and
- (c) fastening at least a portion of the door hardware to the reinforcement plate so that said at least a portion of the door hardware is prevented from relative to the reinforcement plate and away from or along the inner face of the door jamb.

15. A fenestration product reinforcement method as claimed in claim 14; and

- (d) aligning a bolt-receiving opening in the reinforcement plate with a bolt-receiving hole in the door jamb before the former is secured to the latter.

16. A fenestration product reinforcement method as claimed in claim 14, step (a) including the steps of inserting a mounting screw through the reinforcement plate and threading the mounting screw into the door jamb.

17. A fenestration product reinforcement method as claimed in claim 14, step (c) including the steps of inserting an fastening screw through the door hardware and threading the fastening screw into the reinforcement plate.

18. A fenestration product reinforcement method as claimed in claim 14; (d) placing a window jamb alongside the door jamb after step (a) so that the reinforcement plate is located between the door jamb and window jamb; and (e) interconnecting the window jamb and door jamb.

- 18, 19. A fenestration product reinforcement method as claimed in claim
- step (e) including the step of stapling the window jamb and door jamb to one another.

## ABSTRACT OF THE DISCLOSURE

5 A fenestration product includes a door assembly having a door shiftable  
into and out of a closed position, at least one generally flat door jamb presenting an  
inner face that faces inwardly toward the door when the door is in the closed position  
and a generally oppositely facing outer face, and door hardware positioned along the  
inner face of the door jamb and configured to associate the door with the door jamb.  
The product further includes a substantially flat reinforcement plate secured flatly  
against the outer face of the door jamb. Moreover, the door hardware has at least a  
10 portion thereof that is securely fastened to the reinforcement plate so that movement of  
the hardware relative to the door jamb and reinforcement plate is prevented. A method  
of reinforcing a fenestration product in this manner is also disclosed.



Fig. 1.





Fig. 2.







Fig. 5.





Fig. 6.




Fig. 7.




Fig. 8.




Fig. 9.

As a below named inventor I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name, I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHOD AND APPARATUS FOR REINFORCING A DOOR ASSEMBLY

the specification of which: (complete (a), (b) or (c) for type of application)

REGULAR OR DESIGN APPLICATION

- (a) ☒ is attached hereto.  
(b) ☐ was filed on \_\_\_ as Application Serial No. \_\_\_  
and was amended on \_\_\_\_\_ (if applicable).

PCT FILED APPLICATION ENTERING NATIONAL PHASE

- (c) ☐ was described and claimed in International Application No. \_\_\_\_\_ filed \_\_\_\_\_ and  
as amended on \_\_\_\_\_ (if any).

ACKNOWLEDGMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56(a).

- [ ] In compliance with this duty there is attached an information disclosure statement. 37 CFR 1.97.

PRIORITY CLAIM

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:  
(complete (d) or (e))

- (d) ☒ no such applications have been filed.  
(e) ☐ such applications have been filed as follows

EARLIEST FOREIGN APPLICATION(S), IF ANY FILED WITHIN 12 MONTHS PRIOR TO SAID APPLICATION

Country	Application No.	Date of Filing	Date of Issue	Priority Claimed
				<input type="checkbox"/> YES <input type="checkbox"/> NO
				<input type="checkbox"/> YES <input type="checkbox"/> NO
				<input type="checkbox"/> YES <input type="checkbox"/> NO

ALL FOREIGN APPLICATION(S), IF ANY FILED MORE THAN 12 MONTHS PRIOR TO SAID APPLICATION


**PROVISIONAL**

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States application(s) listed below:

Application Serial No.	Filing Date	Status (patented, pending, abandoned)
------------------------	-------------	---------------------------------------

**CONTINUATION-IN-PART**

(Complete This Part Only If This Is A Continuation-In-Part Application)

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose to the Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56(a), which became available between the filing date of the prior application and the national or PCT international filing date of the continuation-in-part application:

Application Serial No.	Filing Date	Status (patented, pending, abandoned)
------------------------	-------------	---------------------------------------

Application Serial No.	Filing Date	Status (patented, pending, abandoned)
------------------------	-------------	---------------------------------------

**POWER OF ATTORNEY**

As a named inventor, I hereby appoint the following attorney(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

Robert D. Hovey	19,223	Steven R. Dickey	32,127
Warren N. Williams	19,156	Thomas H. Van Hoozer	32,761
Stephen D. Timmons	26,513	Andrew G. Colombo	40,565
John M. Collins	26,262	Kyle L. Elliott	39,485
Thomas B. Luebbering	37,874	Tracy L. Bornman	42,347

SEND CORRESPONDENCE TO:  
HOVEY, WILLIAMS, TIMMONS & COLLINS  
2405 Grand, Suite 400  
Kansas City, Missouri 64108

DIRECT TELEPHONE CALLS TO:  
(816) 474-9050

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor	RONALD E. OLBERDING
Inventor's Signature	<i>Ronald E. Olberding</i>
Date	3-18-99
Country of Citizenship	United States
Residence	11118 Oak Street, Kansas City, Missouri 64114
Post Office Address	11118 Oak Street, Kansas City, Missouri 64114

Full name of second joint inventor, if any		DAVID W. ALLEN	
Inventor's Signature <i>David W. Allen</i>			
Date <i>3/18/99</i>		Country of Citizenship United States	
Residence		10116 Hardy, Overland Park, Kansas 66212	
Post Office Address		10116 Hardy, Overland Park, Kansas 66212	